

Grinder - CDD 2.5/3.0 Channel Monster™ - Open channel series

SULZER

The CDD 2.5/3.0 Channel Monster protects pumps and other sensitive equipment by capturing and grinding the toughest wastewater solids in high-flow, heavy solids loading systems. It utilizes two rotating drums to capture solids and direct them to a powerful, dual-shafted, slow-speed, high-torque grinder designed to shred the tough solids that typically cause sewer problems.

Construction

- Open channel configuration
- Grinder cutter stack heights from 1'000 mm to 2'250 mm
- Hardened alloy steel cutters (standard), 191 mm and 222 mm diameter
- Ductile iron housings
- Stainless steel drums with 12.7 mm perforations available in 250 mm, 400 mm or 500 mm diameters
- Hardened alloy steel shafts, 64 mm and 76 mm hex
- Mechanical seals with tungsten carbide faces, 10.3 bar maximum dry working pressure
- Available with channel or wall mounted frame options for easy installation

Performance

- Flow rates up to 9'305 m³/hr

Applications

- Pump stations
- Collection systems
- Headworks at wastewater treatment
- Private facility discharge to municipal sewer system
- Prison sewage system protection

Monster Renew grinder

In place of repairing a worn grinder, choose a Monster Renew unit. Sulzer provides a new, factory-built grinder cartridge to replace the worn grinder cartridge. Remove the motor and reducer from the worn unit, install the motor and reducer on the Monster Renew unit, and install the new assembly in place of the worn unit. Benefits include:

- Minimizes operational downtime
- Quick turnaround
- All new parts
- Great time to upgrade unit
- Full factory warranty on the Monster Renew grinder cartridge

Channel Monster grinder cutters

Tooth count	Thickness	Material
7-tooth	11 mm	Hardened alloy steel
11-tooth	8 mm	Hardened alloy steel



Channel Monster motor assembly

- Single-drive system with 7.5 kW or 11 kW motor powers grinder stack and drums
- Optional multidrive system with one motor to drive grinder stack (7.5 kW or 11 kW) and individual motors for each drum (0.75 kW)
- Optional explosion proof and immersible motors available
- 35:1 reducer, cycloidal design

Channel Monster frame options

- Adapt grinders for easy installation
- Channel frames to fit most channel types
- Wall frames to mount on flat or round walls
- Type 304 or 316 stainless steel construction
- Guide rails for easy installation and maintenance

Channel Monster controller

- Ensures maximum grinding ability with minimum stoppage
- Designed and programmed for specified motor


Channel Monster grinder materials

Part	Standard
Housings	Ductile Iron
Cutters	Hardened alloy steel
Drums	Stainless steel
Shafts	Hardened alloy steel
Mechanical seals	Tungsten carbide faces
Gaskets	Viton™


For guidance in selecting a CDD Channel Monster, please contact Sulzer.

Performance curves

Model CDD 2.5 with 250 mm Drums




Model CDD 2.5 with 400 mm Drums




mm = head drop
 m³/hr = capacity (raw sewage)
 H_{down} = downstream head

Performance curves

Model CDD 2.5 with 500 mm Drums




Model CDD 3.0 with 500 mm Drums



mm = head drop
 m³/hr = capacity (raw sewage)
 H_{down} = downstream head

Dimensions (mm)



Single-drive version shown

Dual drum model	Drum size - mm	B - mm	C - mm	D - mm	W ¹ - mm	Max flow ² - m ³ /hr	Single drive		Multidrive	
							A ³ - mm	Approximate net weight ⁴ - kg	A ³ - mm	Approximate net weight ⁴ - kg
CDD4010-XD2.5	250	1'449	1'168	681	749	1'650	2'558	1'870	2'558	1'919
CDD5010-XD2.5	250	1'695	1'416	681	749	2'195	2'804	1'960	2'804	2'009
CDD6010-XD2.5	250	1'965	1'686	681	749	2'778	3'074	2'074	3'074	2'123
CDD4016-XD2.5	400	1'449	1'168	900	1'060	2'247	2'538	2'210	2'538	2'259
CDD5016-XD2.5	400	1'695	1'416	900	1'060	3'030	2'784	2'323	2'784	2'372
CDD6016-XD2.5	400	1'965	1'686	900	1'060	3'876	3'054	2'459	3'054	2'508
CDD4020-XD2.5	500	1'449	1'168	719	1'365	3'443	2'538	2'505	2'538	2'554
CDD5020-XD2.5	500	1'695	1'416	719	1'365	4'549	2'784	2'630	2'784	2'679
CDD6020-XD2.5	500	1'965	1'686	719	1'365	5'729	3'054	2'777	3'054	2'826
CDD9020-XD3.0	500	2'875	2'486	908	1'365	9'305	Not Available		3'988	4'666

1. For ideal channel construction width add 50 mm.

2. Flow based on optimum channel conditions. Consult factory for analysis of application.

3. Drive dimensions are a maximum based on a unit with a 7.5 kW (IP68) motor. Extended drive shafts are available on request.

4. Weight is based on a unit with a 7.5 kW IP68 drive.

